

RACK MOUNT BRACKETS, 19" EIA

Rack Mount Brackets are designed to mount on 24" and 30" wide open frames. Brackets can be relocated vertically in 1" increments.

Offset Mount Brackets

1. At required mounting height, install two 3-1/4" hanger clips on the left and right sides of the frame. Make sure clips are firmly seated in the hanger frame slots.
2. Install a #10-24 x 3/8" Phillips screw into the top hole of each clip, leaving a 3/16" gap between the underside of the screw head and the face of the clip.
3. With small threaded holes facing inward, align top keyhole slots of Rack Mount Brackets with the top hanger clip screws and slide down over screws to engage. Install two additional screws in the lower holes of the brackets. Securely tighten all screws.
4. Install components on to the Rack Mount Brackets using #10-32 x 5/8" Phillips screws (RMSHP) and 1/4" ID x 1/2" OD washers (RMWHP). These fasteners are not provided with the Rack Mount Brackets; they must be ordered separately.

Flush Mount Brackets

1. At required mounting height, install the Rack Mount Brackets on the left and right sides of the frame. Make sure brackets are firmly seated in the hanger frame slots.
2. Install two #10-24 x 5/8" set screws into the tapped holes on each bracket. Tighten until plate is parallel with the front of the frame.
3. Install components on to the Rack Mount Brackets using #10-32 x 5/8" Phillips screws (RMSHP) and 1/4" ID x 1/2" OD washers (RMWHP). These fasteners are not provided with the Rack Mount Brackets; they must be ordered separately.

3-1/4" Hanger Clip Hardware Pack – HCP3 (#88081901)
Utility Mounting Bracket Hardware Pack – UMBHP (#00050305)

